
Lab 5

Recursivity

Sup'Biotech 3
Python

Pierre Parutto

October 13, 2016



Preamble

Document Property

Authors	Pierre Parutto
Version	1.0
Number of pages	6

Contact

Contact the assistant team at: supbiotech-bioinfo-bt3@googlegroups.com

Copyright

The use of this document is strictly reserved to the students from the Sup'Biotech school. This document must have been downloaded from www.intranet.supbiotech.fr, if this is not the case please contact the author(s) at the address given above.

©Assistants Sup'Biotech 2016.

Contents

1	Introduction	3
2	Warm-up	3
2.1	Dot Product	3
	Example	3
3	Recursivity With Sequences	3
3.1	1 Recursive Case, 1 Stop Case - Pow	3
	Example	3
3.2	1 Recursive Case, 1 Stop Case - A Sequence	3
	Example	4
3.3	1 Recursive Case, 2 Stop Cases - Fibonacci Sequence	4
	Example	4
3.4	2 Recursive Cases, 1 Stop Case - Fast Pow	4
	Example	4
4	Recursivity With Lists	4
4.1	Number Of Elements	4
	Example	5
4.2	Sum Of Elements	5
	Example	5
4.3	Filtering	5
	Example	5
4.4	Inverting A List	5
	Example	5
5	Recursivity With Strings	6
5.1	Distance	6
	Example	6
5.2	Levenshtein Distance	6
	Example	6

1 Introduction

In this sixth lab, we will manipulate recursivity.

2 Warm-up

2.1 Dot Product

I remind you the dot product formula between two vectors $X = X_1, \dots, X_N$ and $Y = Y_1, \dots, Y_N$:

$$X \cdot Y = \sum_{i=1}^N X_i \times Y_i$$

1. Formulate the problem recursively.
2. Write a recursive function `dot_prod_rec(X: list, Y: list) -> int` that computes the dot product between the two vectors X and Y . We consider that X and Y have the same size.

Example

```
>>> dot_prod_rec([1,2], [3,4])
11
>>> dot_prod_rec([4,3], [3,4])
24
```

3 Recursivity With Sequences

3.1 1 Recursive Case, 1 Stop Case - Pow

The power a^b can be computed as:

$$a^b = \begin{cases} a \times a^{b-1} & \text{if } b > 0 \\ 1 & \text{otherwise} \end{cases}$$

Write a recursive function `pow(a: int, b: int) -> int` that returns the value a^b .

Example

```
>>> pow(2,5)
32
>>> pow(4, 8)
65536
```

3.2 1 Recursive Case, 1 Stop Case - A Sequence

Write a recursive function `seq(n: int) -> int` that returns the value u_n of the following sequence:

$$u_n = \begin{cases} 3 \times u_{n-1} - 1 & n = 0 \\ 0 & \text{otherwise} \end{cases}$$

Example

```
>>> seq(1)
-1
>>> seq(3)
-13
```

3.3 1 Recursive Case, 2 Stop Cases - Fibonacci Sequence

Write a recursive function `fibo(n: int) -> int` that returns the n^{th} value of the Fibonacci sequence:

$$F(n) = \begin{cases} 0 & n = 0 \\ 1 & n = 1 \\ F_{n-1} + F_{n-2} & \text{otherwise} \end{cases}$$

Example

```
>>> fibo(2)
1
>>> fibo(11)
89
```

3.4 2 Recursive Cases, 1 Stop Case - Fast Pow

Write a recursive function `fast_pow(a: int, b: int) -> int` that returns a^b using the following formula:

$$a^b = \begin{cases} a \times (a^2)^{\frac{b-1}{2}} & \text{if } b \text{ is odd} \\ (a^2)^{\frac{b}{2}} & \text{if } b \text{ is even} \\ 1 & \text{if } b = 0 \end{cases}$$

Example

```
>>> fast_pow(2, 3)
8
>>> fast_pow(5, 6)
15625
```

4 Recurisivity With Lists

4.1 Number Of Elements

We want to count the numbers of elements in a list.

1. Formulate the problem recursively.
2. Write a recursive function `count(l: list) -> int` that returns the number of elements in the list `l`.

Example

```
>>> count([1,2,3])  
3  
>>> count([1,5,8,6])  
4
```

4.2 Sum Of Elements

We want to sum all the elements in a list.

1. Write the problem recursively.
2. Write a recursive function `sum_list(l: list) -> float` that returns the sum of the elements in the list `l`.

Example

```
>>> sum_list([1,2,3])  
6  
>>> sum_list([-1.5, 0.8, 1.2])  
0.5
```

4.3 Filtering

We want to remove all the odds elements from a list.

1. Formulate the problem recursively.
2. Write a recursive function `filter_odd(l: list) -> list` that returns the list `l` **without** all the odd elements.

Example

```
>>> filter_odd([1, 2, 3])  
[2]  
>>> filter_odd([7, 9, 11])  
[]
```

4.4 Inverting A List

We want to invert the elements of a list.

1. Formulate the problem recursively.
2. Write a recursive function `invert(l: list) -> float` that return the list `l` inverted (the first element becomes the last, etc).

Example

```
>>> invert([1, 2])  
[2, 1]  
>>> invert([5, 4, 3, 2, 1])  
[1, 2, 3, 4, 5]
```

5 Recursivity With Strings

5.1 Distance

A measure of the distance between two strings is defined as:

$$D(s_1, s_2) = \begin{cases} |s_1| & \text{if } s_2 \text{ is empty} \\ |s_2| & \text{if } s_1 \text{ is empty} \\ D(\text{suffix}(s_1), \text{suffix}(s_2)) & \text{if } s_1[0] = s_2[0] \\ 1 + D(\text{suffix}(s_1), \text{suffix}(s_2)) & \text{if } s_1[0] \neq s_2[0] \end{cases}$$

where $|x|$ is the length of the sequence x and $\text{suffix}(x)$ is the sequence x **without the first character**.

Write a recursive function `dist_str(s1: str, s2: str) -> int` that returns the distance D between the two sequences s_1 and s_2 . The two sequences can have different lengths.

Example

```
>>> dist_str("AAAAAA", "")  
5  
>>> dist_str("AAAAAA", "ATGC")  
4
```

5.2 Levenshtein Distance

The Levenshtein distance (also called edit distance) between two strings is defined as:

$$L(s_1, s_2) = \begin{cases} L(\text{suffix}(s_1), \text{suffix}(s_2)) & \text{if } s_1[0] = s_2[0] \\ \min \begin{cases} 1 + L(\text{suffix}(s_1), \text{suffix}(s_2)) & \text{if } s_1[0] \neq s_2[0] \\ 1 + L(s_1, \text{suffix}(s_2)) \\ 1 + L(\text{suffix}(s_1), s_2) \end{cases} & \text{if } s_1[0] \neq s_2[0] \\ |s_1| & \text{if } |s_2| = 0 \\ |s_2| & \text{if } |s_1| = 0 \end{cases}$$

where $|x|$ is the length of the sequence x and $\text{suffix}(x)$ is the sequence x **without the first character**.

Write a recursive function `levenshtein(s1, s2)` that returns the Levenshtein distance between the two sequences s_1 and s_2 .

Example

```
>>> levenshtein("ATTGT", "")  
5  
>>> levenshtein("ATTGT", "AT")  
3  
>>> levenshtein("AATTTGTC", "ATTGT")  
3
```